

4 IN 1 IR MEDIUM/HIGH SPEED DOME CAMERA



2/5
MP RESOLUTION

PAN / TILT

AUTO FLIP

With
Starlight
TECHNOLOGY

Features

- OSD menu is available
- Keep original analog system
- AHD/TVI/CVI/CVBS selectable
- Real time transmission, lossless video
- Long distance transmission up to 300 meters
- 17.78cm (7) Half Metal Housing, IP66 rate protection

Specification	S-PTZ-D2A-36X-240M (2MP)	S-PTZ-D5A-20X-240M (5MP)
Sensor	1/3" CMOS 2MP NVP2441+SONY307	1/2.7" CMOS 5MP NVP2477 + OV05A10
Output pixels	1920x1080/30fps, 1920x1080/25fps	2688 x 1944 @22fps, 2688 x 1944 @15fps
Lens	36X 4.6mm~165mm	20X, F= 4.7- 96.3mm
BLC	Support	
AGC	Auto/Manual	
WB	Indoor/Outdoor/Auto/Manual	
S/N Ratio	>50dB	
D-WDR	Support	
Rotation Range	Pan: 0°~360°, Tilt: 0°~93°	
Rotation Speed	Pan: 0~200°/s, Tilt:0~100°/s	Pan: 0~80°/s, Tilt:0~40°/s
Auto Control IR LED	PWM	
IR distance	Up to 240 meters	
IR LED	9PCS IR LED, 4pcs IR Laser LED	
Auto Flip	Horizontal 180°, Vertical 93°	
Preset Points	220pcs preset (Dwell Preset 01-60s interval available)	
A-B Scan	User programmable (scan speed 1-64 levels setting available)	
Guard Tours	3 groups (Max. 16 points, dwell time user selectable)	
Video interface output	AHD/TVI/CVI/CVBS selectable	
Communication mode	RS485 (+/-) / coaxial cable	
Operating Temp.	-40°C~+60°C	
Power	DC12V 4A	
Power Consumption	≤25W	
Lightning Protection	Transient voltage 6000V	

