

# 4 IN 1 PTZ BULLET Camera



## Features

- OSD menu is available
- Total Metal housing, IP66
- A-B scan, tour available
- Support coaxial function
- Real time transmission, lossless video
- Support AHD / TVI / CVI / CVBS output



Specification	S-PTZ-W2A-10X-100M
Sensor	1/3" CMOS 2MP NVP2441 + SONY 323
Output pixel	1920x1080p/30fps, 1920x1080p/25fps
Lens	10X f=5.1mm~51mm
WB	Auto/Indoor/Outdoor/Manual
BLC	Support
AGC	Auto/Manual
S/N Ratio	>50dB
IR distance	Up to 100 meters
LEDs	4PCS IR + 2PCA laser LED
Rotation Range	Pan:0°~200°, Tilt:~45°~40°
Rotation Speed	Pan:0~30°/s, Tilt:0~25°/s
Auto Flip	Support
Preset Points	220pcs preset (Dwell time 01-60s interval available)
Guard Tours	3 groups (each group 16 preset, dwell time and speed selectable)
AB scan range	Any Point in range; 45-40(Tilt) and 0-200(Pan)
AB scan speed	1-9 grades
Signal Transfer	AHD/CVI/TVI/CVBS selectable
Operating temp.	-40°C~+60°C
Consumption	≤ 15W
Power	12V 2A (Not included)
Related validation	IP66, CE, FCC, RoHs