

2MP IP Bullet Camera

50M IR, White Light, PoE,
Audio, 4mm



SP-C2QN-I5W
Color Master Series

KEY FEATURES

- Metal+Plastic Housing
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. Illumination Color: 0.02Lux@F1.6
- 2 Warm Lights, 15m
- Smart IR, IR Range: 50m
- Built-in Mic
- Operating Conditions: -30°C ~ 60°C, 0 ~ 95% RH
- Support Tripwire and Perimeter
- POE, IP67




Camera	
Image Sensor	1/2.8"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON), B/W:0Lux with IR
Shutter Time	1s-1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
WDR	DWDR
S/N	>39dB
Angle Adjustment	0-360°; 0-80°; 0-360°
Lens	
Lens Type	Fixed
Focal Length	4mm
Lens Mount	M12
Aperture Range	F1.6,Fixed
Field of View	87.7°(H); 45°(V); 98.6°(D)
DORI Distance	Detect: 55.1m Observe: 21.8m Recognize: 11.0m Identify: 5.5m
Illuminator	
IR LEDs	2
IR Distance	50m
Wavelength	850nm
White LEDs	2
Whitelight Distance	15m
Compression Standard	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k-6Mbps
Audio Compression	G.711A/G.711U/ADPCM_D
Audio Sampling Rate	8kHz/32kHz/48kHz

Image	
Max. Resolution	1920x1080@30fps
Main Stream	PAL: 25fps(1920x1080, 1280x720, 640x480, 704x576) NTSC: 30fps(1920x1080, 1280x720, 640x480, 704x480)
Sub Stream	PAL: 25fps(704x576, 704x288, 640x360, 352x288) NTSC: 30fps(704x480, 704x240, 640x360, 352x240)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-auto/Manual/Sunny/Natural light/Warm light/Sodium lamp/Incandescent lamp/Locked white balance
ROI	8 regions
OSD	1regions; 16*16/32*32/48*48
Privacy Mask	4 regions
Defog	Yes
Feature	
Alarm Trigger	Motion Detection; Mask Alarm: IP Address Conflict
Linkage Method	Trigger Warmlight; Trigger Capture
Video Analytics	Tripwire; Perimeter

Network	
Protocols	HTTP; HTTPS; TCP/IP; UDP; UPnP; ICMP; DHCP; DNS; DDNS; Easy DDNS; NTP; QoS; Ipv4; SSH; Unicast; RTSP; FTP
System Compatibility	P2P(Mutually exclusive with Profile G); Onvif Profile S/T; CGI; MIL STONE
Remote Connection	<2
PC CMS Software	Secureye Smart Client
Mobile APP	Phoenix Pro
Web	IE10+:Firefox52+; Edge89+; Safari11+; Chrome57+
Interface	
Communication Interface	1RJ45 10M/ 100M self adaptive Ethernet port
Built-In Mic	Yes
General	
Web Client Language	English/Spanish/Italian/Turkish French/Polish/German/Ukrainian
Operating Temperature	-30°C-60°C
Operating Humidity	0-95%
Storage Temperature	-30°C-60°C
Storage Humidity	0-95%(non-condensing)
Power Supply	DC12V+25%, MAX 6.5W; POE 802.3af, MAX 7W
Protection	Surge protection 2000V; Lightning Proof 6000V; Ip67
Boundary Dimensions	164(L)73(W)73(H)mm
Package Dimensiond	180(L)90(W)95(H)mm
GrossWeight	0.3Kg
NetWeight	0.25Kg

DIMENSIONS (Unit: mm)



ACCESSORIES

